



**Tel:** 800-752-9326  
**Fax:** 763-389-2725  
**SRWProducts.com**

PO Box 70  
 32005 126th St  
 Princeton, MN 55371

## CC-4 100% Coconut Blanket

### Double Sided Net

SRW CC-4 Coconut extended term Erosion Control Blankets consist of 100% coconut fibers manufactured into a continuous matrix. The coconut fiber matrix is confined by a photodegradable, synthetic net on top and bottom, mechanically (stitch) bound on two-inch centers. SRW CC-4 is intended for applications requiring up to 36 months of functional longevity. Actual field longevity is dependent on soil and climate conditions.

SRW CC-4 Coconut Blankets meet or exceed the physical property values listed below.

Physical Property	Test Method	Minimum Average Roll Value		
Matrix		100% Coconut Fibers		
Netting Material		Polypropylene (Double Sided)		
Netting Type		Extended-Term Photodegradable		
Mass/Unit Area	ASTM D 6475	9.5 oz/yd <sup>2</sup>		
Blanket Life (Avg)		24-36 months		
Slope Rating	ASTM D 6459	1:1 or greater		
Tensile Strength (MD)	ASTM D 6818	220.8 lb/ft		
Elongation (MD)	ASTM D 6818	25%		
Light Penetration	ASTM D 6567	15% Open		
Water Absorption	ASTM D 1117	250%		
Net Opening Dimensions		0.7 in x 0.7 in (Top Net) 0.7 in x 0.7 in (Bottom Net)		
Roll Sizes	Sq Yds / Roll	Size	Roll Weight	Qty Per Pallet
FCMB C081125	100.00	8' x 112.5'	60 lbs	30

Values Provided represent expected values at time of manufacture. This document provides the characteristic properties of the product described.